
U N I C O R D E R
Option for U-228
U - 2 2 8 - M R K

SPECIFICATION

Specifications are subject to change without notice.

Create				P A N T O S C O . , L T D		
Contents	September 25, 2017					
Text	1	Wtiting	Check	Approve	Document number	Rev.
Figure		Kojima	Okuyama	Okuyama	228MRK-00-0001	
Cover	1					

Outline

Besides a recording pen of the main unit, a device makes it possible to place a mark in the right end part of recording paper by using an exclusive-use pen.

It is possible to place an arbitrary mark on a time axis.

Specifications

M o d e l		U-228-MRK		
C h a n n e l		1	2	
Event marker (Another pen type)	Reference position	Marker space on right side of recording paper. 2 mm to the right from the right end. The position of the time axis is collinear with the recording pen.	Marker space on right side of recording paper. 2 mm to the right from the right end. The position of the time axis is collinear with the recording pen of channels 2. (4 mm anterior of the recording pen of channel 1)	
	Amplitude	2 ± 0.5 mm to the left from the above reference position. (When operating, the marker space is on the right.)		
	※ 1 Operation method	Same as external contact short circuit time		
	External contact capacity	DC 20V, More than 0.8A		
	Marker pen	Cartridge type Fiber chip pen		
			Red	Green
※ 2 Pen lift	Interlocking movement with recording pen	Interlocking movement with recording pen of channel 2		
Accessory	Marker pen	NDE-10R (Red) 1	NDE-10G (Green) 1	
	※ 3 Recording pen	NDC-18R (Red) 1		
	External operation connector	Plug for Another pen marker 1	Plug for Another pen marker 1	

※ 1 Operation by short-circuiting pins 5 and 6 of external operation connector.

※ 2 The amount of pen up is 1.0 mm or more.

※ 3 For 1 channel recorder, change the accessory recording pen NDA-5R (Red) to NDC-18R (Red) .