
U N I C O R D E R
Option for U-329
U - 3 2 9 - M R K

SPECIFICATION

Specifications are subject to change without notice.

Create				P A N T O S C O . , L T D		
Contents	September 25, 2017					
Text	1	Wtiting	Check	Approve	Document number	Rev.
Figure		Kojima	Okuyama	Okuyama	329MRK-00-0001	
Cover	1					

Outline

Besides a recording pen of the main unit, a device makes it possible to place a mark in the right end part of recording paper by using an exclusive-use pen.

It is possible to place an arbitrary mark on a time axis.

Specifications

M o d e l		U-329-MRK
Event marker (Another pen type)	Reference position	Marker space on right side of recording paper. The position of the time axis is 4 mm backward of the recording pen of channel 1.
	Amplitude	2 ± 0.5 mm to the left from the above reference position. (When operating, the marker space is on the right.)
	※ 1 Operation method	Same as external contact short circuit time
	External contact capacity	DC 20V, More than 0.8A
	Marker pen	Cartridge type Fiber chip pen (Red)
	※ 2 Pen lift	Interlocking movement with recording pen of channel 1.
Accessory	Marker pen	NDE-10R (Red) 1
	External operation connector	Plug for Another pen marker 1

※ 1 Operation by short-circuiting pins 5 and 6 of external operation connector.

※ 2 The amount of pen up is 1.5 mm or more.